

WWW.DELOCK-LIGHTING.COM





DATA SHEET

LED light bar triangular V2 100cm with 144 SMD LED white

Description

With the energy saving LED light bar it is possible to create beautiful light effects, e.g. under cabinets or behind paintings. Thanks to the included mounting clips the installation is very easy. The light bars can be connected with each other using the included connectors or connection cables.



Ref. 46272

EAN 4043619462728

Country of origin China
Customs tariff number 94054039

Images



Specification

• Operating voltage: 24V DC

Light bar with 144x SMD3528 LED in white

Power consumption: 10.0WCurrent demand: 420mA

Color temperature: ca. 4000K
Luminous flux: 700 Lumen
Light intensity: 280 Lux / 1m

Beam angle: 90°Protection class: IP20

• Dimensions: 1000x33x20mm (l/w/h)

Package content

- · LED light bar
- Plastic connector
- Connection cable
- Mounting clamps & screws
- Manual

Package

Color Box

Optional accessory

Item 46260: Power supply 12W incl. connection cable Item 46262: Power supply 12W incl. connection cable

Item 46274: 4-fold distributor Item 46275: 8-fold distributor

24 | = 10.0 | 420 | IP | 10.0 | M | M | 10 | M |

^{© 2011} by Delock Lighting. Alle hier aufgeführten Namen und Zeichen sind Eigentum des jeweiligen Herstellers. Druckfehler, Änderungen & Irrtümer vorbehalten.